

# La gamma più completa di PARACADUTE - The complete range of SAFETY GEARS

## IN-3000



Paracadute istantaneo

*Instantaneous safety gear*

For tripping speed 1 m/s

P+Q max. Guide 8 = 2480 kg

P+Q max. Guide 9 = 2837 kg

Guide rail type: cold drawn and oiled or dry

Admissible guide rail thickness: 8 and 9 mm

## IN-6000



Paracadute istantaneo

*Instantaneous safety gear*

For tripping speed 1 m/s


P+Q max. Cold-drawn guide rail = 6601 kg

P+Q max. Machined guide rail = 5295 kg

Guide rail type: cold drawn or machined and oiled or dry

Admissible guide rail thickness: 16 mm

## PR-2000-UD



Paracadute a presa progressiva bidirezionale

*Bidirectional progressive safety gear*

Min P+Q = 537 kg

Max P+Q = 1222 kg

Max tripping speed = 2,0 m/s

Guide rail type: cold drawn and oiled

Admissible guide rail thickness: 5 to 16 mm

Min gripping width = 25 mm Fulfills EN-81+A3

## PR-2500-UD-V.50



Paracadute a presa progressiva bidirezionale

*Bidirectional progressive safety gear*

Min P+Q = 613 kg

Max P+Q = 1955 kg


Max tripping speed = 2,5 m/s

Guide rail type: cold drawn or machined and oiled

Admissible guide rail thickness: 7 to 16 mm

Min gripping width = 25 mm Fulfills EN-81+A3

## PQ-3400-UD



Paracadute a presa progressiva bidirezionale

*Bidirectional progressive safety gear*

Min P+Q = 1107 kg


Max P+Q = 3304 kg

Max tripping speed = 2,5 m/s

Guide rail type: machined and dry

Admissible guide rail thickness: 8 to 16 mm

## PQ-4000-UD



Paracadute a presa progressiva bidirezionale

*Bidirectional progressive safety gear*

Min P+Q = 2173 kg

Max P+Q = 4023 kg

Max tripping speed = 2,5 m/s

Guide rail type: machined and oiled

Admissible guide rail thickness: 8 to 16 mm

## ASG-100/ASG-120



Paracadute a presa progressiva

*Progressive safety gear*

	ASG-100 ASG-100UD	ASG-120 ASG-120 UD	ASG-121 ASG-121 UD	ASG-65 ASG-65 UD
	Cold-drawn Oiled	Machined Oiled	Machined Dry	Cold-drawn Oiled
Permissible mass				
Min	515 kg	693 kg	598 kg	782 kg
Max	2139 kg	4233 kg	4019 kg	2214 kg
Max tandem conf.	4278 kg	8466 kg	8038 kg	4428 kg
Admissible guide rail thickness			7 to 16 mm	8 mm
Min gripping width			25 mm	20 mm
Max tripping speed			2,33 m/s	2,33 m/s

## TANDEM ASG+T25



FULFILLS EN-81+43

Paracadute a presa progressiva

*Progressive safety gear*

*Distance between guides: from 600 to 3000 mm  
(if other distances are needed, pls. contact us).*

*Safety switch (optional).*



For info please contact us :  
**info@ilclift.com**  
**ILC srl Via Alessandrini, 17/19**  
**20013 Magenta MI Italy**